

L-SEALERS ESA PROFESSIONAL SERIES

MODELS

ESA2016TK, ESA2028TK, ESA2040TK, ESA2050TK, ESA2070TK, ESA2080TK, ESA20100TK, ESA3040TK, ESA3050TK, ESA3070TK, ESA3080TK, ESA30100TK, ESA4040TK, ESA4050TK, ESA4070TK, ESA4080TK, ESA40100TK, ESA050TK, ESA5070TK, ESA5080TK, ESA50100TK

DURABILITY THAT CAN'T BE MATCHED

EASTEY's Professional Series ESA L-Sealers provide top of the line features and the most robust L-Sealer design on the market today. Expertly welded from ¼" cold rolled steel, EASTEY Professional ESA L-Sealers will withstand even the most abusive real world sealing applications. As a measure of strength, EASTEY L-Sealers weigh nearly twice as much as competitive models.

PROVEN RELIABILITY FOR YOUR NEEDS

Eastey L-Sealers are designed and built to give you all the performance features needed for positive sealing a wide variety of films including polyolefin, polyethylene, and PVC. Cast seal arms, pneumatic operation, stainless steel film clamps, and heavy-duty magnet clamping are just some of the features that provide the durability you have come to rely on from EASTEY. See for yourself why EASTEY has been a leader in the shrink packaging industry for over 25 years.

PNEUMATIC SEMI-AUTOMATIC L-SEALING EASTEY ESA Professional Series L-Sealers are the ultimate workhorse for your most abusive sealing applications.

STANDARD FEATURES

- Designed to seal most polyolefin, polyethylene, and PVC* shrink films
- All-welded main frame from 1/4" cold rolled steel
- Built-in drawer for tools or spare parts
- Seal head casting equipped with head return cylinder
- Stainless steel film clamps hold film in place while sealing
- Dual palm pneumatic seal head activation
- Hot knife seal systems available with mushroom (standard), pancake, or arrow inserts
- Dual locking magnet clamps apply even pressure across sealbar
- Adjustable dwell time for better seal control
- Solid state temperature control adjustable for a variety of films
- Adjustable product tray accommodates wide variety of product sizes
- Takeaway conveyor can be raised or lowered to center-seal product
- Automatic takeaway conveyor
- Heavy duty film cradle allows for easy changeovers and adjustments
- Adjustable pin perforator provides air evacuation
- Side seal size from 20" 50"; front seal size from 16" 100"
- Maximum film width up to 44"
- Maximum film roll OD up to 12"; 10" with power unwind
- Custom two-part epoxy finish resists scratching
- Heavy duty casters for transportation within plant
- Available in 110v, 220v, or optional 480v
- 60-80 psi air requirement
- Easy to use design requires minimal training and maintenance
- Made in the USA



STANDARD FEATURES





















bu - bu psi dir connection manifold











PROFESSIONAL SERIES



A Power film unwind

Allows free feeding of film increasing operator efficiency.

B Film Inverter

Inverting head allows the film to come off the back of machine. This pre-opens the film and minimizes operator effort which in turn increases output.

C Hot Knife Inserts

Hot knife inserts available in Mushroom, Pancake, or Arrow styles.

- D Left Hand Models Available
- E DuoSeal Continuously Heated Seal Bar
- F Lower Conveyor
- G Customer Product Guides and/or Product Tray

L-SEALERS ESA PROFESSIONAL SERIES

MODEL NUMBER	SEAL DIMENSIONS		MACHINE DIMENSIONS			STANDARD POWER				
	FRONT	SIDE	WIDTH	HEIGHT	LENGTH	VOLTS	AMPS	PHASE	WEIGHT	SHP WT.
ESA2016TK	16″	20″	34″	44″	63″	220/110	10/20	1	600 lbs	700 lbs
	41 cm	51 cm	86 cm	112 cm	160 cm				272 kg	317 kg
ESA2028TK	28″	20"	34″	44″	84″	220/110	10/20	1	700 lbs	800 lbs
	71 cm	51 cm	86 cm	112 cm	213 cm				317 kg	362 kg
ESA2040TK	40″	20″	34″	44″	106″	220	15	1	800 lbs	900 lbs
	102 cm	51 cm	86 cm	112 cm	269 cm				362 kg	408 kg
ESA2050TK	50″	20″	34″	44″	126″	220	20	1	900 lbs	1000 lbs
	127 cm	51 cm	86 cm	112 cm	320 cm				408 kg	453 kg
ESA2070TK	70″	20″	34″	44″	167″	220	25	1	1300 lbs	1400 lbs
	178 cm	51 cm	86.36	112 cm	424 cm				589 kg	635 kg
ESA2080TK	80″	20″	34″	44″	187″	220	20	1	1500 lbs	1600 lbs
	203 cm	50 cm	86 cm	112 cm	474 cm				680 kg	725 kg
ESA20100TK	100″	20″	34″	44″	227″	220	20	1	1900 lbs	2000 lbs
	254 cm	50 cm	86 cm	112 cm	577 cm				861 kg	907 kg
ESA3040TK	40″	30″	43″	44″	106″	220 20	20	1	1200 lbs	1300 lbs
	101.60	76.20	109 cm	112 cm	269 cm	220	20	1	544 kg	591 kg
ESA3050TK	50″	30″	43″	44″	126″	220	20	1	1300 lbs	1400 lbs
	127 cm	76 cm	109 cm	112 cm	320.04	220	20	'	591 kg	637 kg
ESA3070TK	70″	30″	43″	44″	167″	220	25	1	1600 lbs	1700 lbs
	177 cm	76 cm	109 cm	112 cm	424 cm				728 kg	774 kg
ESA3080TK	80″	30″	43″	44″	187″	220	25	1	1800 lbs	1900 lbs
	203 cm	76 cm	109 cm	112 cm	474 cm				819 kg	861 kg
ESA30100TK	100″	30″	43″	44″	227″	220	25	1	2100 lbs	2200 lbs
	254 cm	76 cm	109 cm	112 cm	577 cm				956 kg	997 kg
ESA4040TK*	40″	40″	53″	44″	106″	220	20	1	1700 lbs	1800 lbs
	101 cm	101 cm	135 cm	112 cm	269 cm				774 kg	819 kg
ESA4050TK*	50"	40″	53″	44″	126″	220	20	1	1900 lbs	2000 lbs
	127 cm	101 cm	135 cm	112 cm	320 cm				861 kg	907 kg
ESA4070TK*	70″	40″	53″	44″	167″	220	25	1	2100 lbs	2200 lbs
	177 cm	101 cm	135 cm	112 cm	424 cm				956 kg	997 kg
ESA4080TK*	80″	40″	53″	44″	187″	220	25	1	2300 lbs	2400 lbs
	203 cm	101 cm	135 cm	112 cm	474 cm				1043 kg	1092 kg
ESA40100TK*	100″	40″	53″	44″	227″	220	25	1	2600 lbs	2700 lbs
	254 cm	101 cm	135 cm	112 cm	577 cm				1179 kg	1229 kg
ESA5050TK*	50″	50"	63″	44″	126″	220	20	1	1900 lbs	2000 lbs
	127 cm	127 cm	160 cm	112 cm	320 cm				861 kg	907 kg
ESA5070TK*	70″	50"	63″	44″	167″	220	25	1	2100 lbs	2200 lbs
	177 cm	127 cm	160 cm	112 cm	424 cm				956 kg	997 kg
ESA5080TK*	80″	50″	63″	44″	187″	220	25	1	2300 lbs	2400 lbs
	203 cm	127 cm	160 cm	112 cm	474 cm				1043 kg	1092 kg
ESA50100TK*	100	50"	63″	44″	227″	220	25	1	2600 lbs	2700 lbs
	254.00	127 cm	160 cm	112 cm	577 cm				1179 kg	1229 kg



All machines require a 60-80 psi air connection * Powered film unwind included

 7041 Boone Avenue North, Brooklyn Park, MN 55428

 (763) 428-4846
 1 (800) 835-9344

 www.eastey.com
 info@eastey.com



E N G A G E technologies corporation